

### **Amendments to and Listing of Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently amended) An ergonomic handle comprising:  
a main body portion; and  
an appendage support member projecting laterally from the main body portion, the  
appendage support member comprising a top surface that provides a concave  
recess wherein a principle axis of the concave recess passing through a  
center of curvature and a vertex of the concave recess is substantially  
perpendicular to and offset from a centerline of the main body portion, and a  
substantially continuous convex shaped bottom surface configured to  
provide a ergonomic support surface for an appendage of a user.
2. (Currently amended) The handle as claimed in claim 1 wherein the appendage  
support member accommodates an ergonomic placement of both a distal portion of a first  
appendage of a hand of a the user adjacent the concave recess of the top surface of the  
appendage support member and a distal portion of a second appendage of the hand of the  
user adjacent a the substantially continuous convex bottom surface of the appendage  
support member, wherein upon a grasping of the main body portion by the user, the distal  
portions of the user's first and second appendages are supported by the appendage support  
member and are fully offset from ~~a lateral~~ the centerline of the main body portion.
3. (Previously presented) The handle as claimed in claim 2 wherein the first  
appendage is a thumb on the hand of the user.
4. (Previously presented) The handle as claimed in claim 3 wherein the second  
appendage is an index finger on the hand of the user.

5. (Previously presented) The handle as claimed in claim 3 wherein the concave recess comprises a support surface and peripheral wall portions for accommodating and locating the user's thumb, the peripheral wall portions providing resistance to sliding movement of the thumb relative to the support member.

6. (Previously presented) The handle as claimed in claim 5 wherein the concave recess is dimensioned for a close fit with the thumb.

7. (Previously presented) The handle as claimed in claim 6 wherein the main body portion comprises a first thin portion near a proximal end of said handle, a second thin portion near a distal end of said handle, and a broad portion between the first and second thin portions, and wherein the broad portion is thicker in cross section than the first and second thin portions, and further wherein the change in the cross sectional thickness between each of the portions is gradual.

8. (Currently amended) A knife comprising:

- a blade member having a cutting edge; and

- a handle comprising:

- a main body portion; and

- an appendage support member projecting laterally from the main

- body portion, the appendage support member comprising a top surface that includes a concave recess wherein a principle axis of the concave recess passing through a center of curvature and a vertex of the concave recess is substantially perpendicular to and offset from a centerline of the main body portion, and a substantially continuous convex shaped bottom surface configured to provide a ergonomic support surface for an appendage of a user.

9. (Currently amended) The knife as claimed in claim 8 wherein the appendage support member accommodates an ergonomic placement of both a distal portion of a first appendage of a hand of a the user adjacent the concave recess of the top surface of the appendage support member and a distal portion of a second appendage of the hand of the user adjacent a the substantially continuous convex shaped bottom surface of the appendage support member, wherein upon a grasping of the main body portion by the user, the distal portions of the user's first and second appendages are supported by the appendage support member and are fully offset from a-lateral the centerline of the main body portion.

10. (Previously presented) The knife as claimed in claim 9 wherein the first appendage is a thumb on the hand of the user.

11. (Previously presented) The knife as claimed in claim 10 wherein the second appendage is an index finger on the hand of the user.

12. (Previously presented) The knife as claimed in claim 10 wherein the concave recess comprises a support surface and peripheral wall portions for accommodating and locating the user's thumb, the peripheral wall portions providing resistance to sliding movement of the thumb relative to the support member.

13. (Previously presented) The knife as claimed in claim 12 wherein the concave recess is dimensioned for a close fit with the thumb of an average adult.

14. (Previously presented) The knife as claimed in claim 13 wherein the main body portion comprises a first thin portion near a proximal end of said handle, a second thin portion near a distal end of said handle, and a broad portion between the first and second thin portions, and wherein the broad portion is thicker in cross section than the first and second thin portions, and further wherein the change in the cross sectional thickness between each of the portions is gradual.

15. (Currently amended) A hand implement comprising:  
an tool member for performing the particular function of the implement; and  
a handle comprising:  
a main body portion; and  
an appendage support member projecting laterally from the main  
body portion, the appendage support member comprising a  
top surface with a concave cavity wherein a principle axis of  
the concave cavity passing through a center of curvature and  
a vertex of the concave cavity is substantially perpendicular  
to and offset from a centerline of the main body portion, and  
a substantially continuous convex shaped bottom surface  
configured to provide a ergonomic support surface for an  
appendage of a user.

16. (Currently amended) The hand implement as claimed in claim 15 wherein the  
appendage support member accommodates an ergonomic placement of both a distal portion  
of a first appendage of a hand of a the user adjacent the concave cavity of the top surface of  
the appendage support member and a distal portion of a second appendage of the hand of  
the user adjacent a the substantially continuous convex shaped bottom surface of the  
appendage support member, wherein upon a grasping of the main body portion by the user,  
the distal portions of the user's first and second appendages are supported by the appendage  
support member and are fully offset from a ~~lateral~~ the centerline of the main body portion.

17. (Previously presented) The hand implement as claimed in claim 16 wherein the  
first appendage is a thumb on the hand of the user.

18. (Previously presented) The hand implement as claimed in claim 17 wherein the  
second appendage is an index finger on the hand of the user.

19. (Previously presented) The hand implement as claimed in claim 17 wherein the concave cavity comprises a support surface and peripheral wall portions for accommodating and locating the user's thumb, the peripheral wall portions providing resistance to sliding movement of the thumb relative to the support member.

20. (Previously presented) The hand implement as claimed in claim 19 wherein the concave cavity is dimensioned for a close fit with the thumb.

21. (Previously presented) The hand implement as claimed in claim 20 wherein the main body portion comprises a first thin portion near a proximal end of said handle, a second thin portion near a distal end of said handle, and a broad portion between the first and second thin portions, and wherein the broad portion is thicker in cross section than the first and second thin portions, and further wherein the change in the cross sectional thickness between each of the portions is gradual.